



DryTec®

Calcium Hypochlorite Briquettes

Versatile and effective, **DryTec® Calcium Hypochlorite Briquettes** provide effective sanitizing and disinfecting solutions. **DryTec®** is one of the best industrial strength chlorinators on the market today, providing solutions in a variety of industrial sectors including water treatment facilities, pulp & paper, tanneries and more.

THE BENEFITS INCLUDE

- Contains 66% available chlorine
- Cost effective
- Effective alternative to gas and liquid hypochlorite
- Convenient and easy to use
- Supplied in 50 lb. plastic pails
- Requires no storage tanks or secondary containment
- Small pillow-shaped briquettes provide an optimum spray bed pack resulting in outstanding solution consistency



PATENTED PILLOW-SHAPED
BRIQUETTES



DELIVER UNPARALLELED
CONSISTENT RESULTS



drytec®

DryTec® Calcium Hypochlorite Briquettes

DryTec® Calcium Hypochlorite Briquettes are unique because they have applications in a host of industries. Versatile and effective, **DryTec® Briquettes** provide unparalleled industrial sanitizing and disinfecting solutions.

APPLICATIONS

- **Industrial Water Treatment**
 - Controls slime growth and maximizes efficiency in cooling towers, ponds and reservoirs
 - Controls slime growth, improves efficiency and reduces unpleasant odors in commercial A/C systems
- **Potable Water**
 - Hypochlorination for disinfecting small community water supplies
 - Low initial investment
 - Maintains economical operating costs
- **Private Water Supplies**
 - Sanitizes wells, natural springs, cisterns and storage tanks by destroying harmful microbes
 - Purifies by destroying harmful organic matter
- **Industrial Cyanide Waste**
 - Oxidizes toxic cyanides, producing harmless cyanates
- **Pulp & Paper**
 - Effective bleaching agent for all common paper dyes
- **Restaurant**
 - Kills bacteria on dishes, glasses and other eating utensils
- **Tanneries**
 - Effective bleaching agent which removes coloring matter from wooden drums used in dyeing leather
 - Controls bacterial activity and odors in tanning waste liquors

TYPICAL PROPERTIES

	Minimum	Maximum
• Available Chlorine (% by weight)	65.00	-
• Water (% by weight)	4.0	8.5
• Iron (% by weight)*	-	0.05
• Oxides, heavy metals & Al* (% by weight)	-	0.5
• Scale Inhibitor* (target % by weight)	0.4	0.6
• Weight (grams)*	6.0	8.0
• Dimension (mm - approx.)*	-	32 x 19 x 13

* The above values are typical. Actual sizes, weights and composition may vary.

REGULATORY

- EPA No. 1258-1179
- NSF Standard 60, Drinking Water Additives
- Meets AWWA Standard B300-04

PACKAGING

DryTec® Chlorinator Briquettes are available in 50 lb. plastic pails



CALL 1-800-478-5727

to find out more about
DRYTEC® BRIQUETTES
or visit our website at
www.archwaterworks.com/industrial



Versatile. Effective. Reliable.



Arch Chemicals, Inc.
1955 Lake Park Drive, Suite 100
Smyrna, GA 30080
1-800-478-5727